

## **STYLE BETON**

Nano Top (Self Leveling Floor) — Nano Top Vertical

DESCRIPTION	Style Beton Nano Top is a unique material that can be applied on existing floorings to avoid costs of demolition fast and easy. Nano Top is a unique powder mixture of polymer, cement and other aggregates. It is recommended for resurfacing, mostly interiors but also exteriors. Available in bags of 20 kg.  The material can be applied, after we spread the surface with Style Acrylic Primer, using a squeegee onto the surface at a thickness of approximately 1-2 mm (the thickness of a credit card).
Colors	The standard color for Nano Top is white but upon request may be made available in various colors such as grey, terracotta, etc. which can also be combined to each other and create a "unique game of colors" or after the floor is completely dry, it can be applied Acid Stain.
Restrictions	The temperature must not be below 5 ° C and above 25 ° Celsius.
Packaging	20 kg bags.
Storage	At room temperature onto pallets. Protect from moisture and freezing temperatures.
Application	Mix 20kg of Nano Top with 5 lt fresh and clean water using low speed mixing. The material can be applied with a squeegee or roller onto the surface at a thickness of approximately 1-2 mm (the thickness of a credit card).
	The Nano Top can be applied very easily, with one-step application, to interior floor, wall (Nano Top Vertical) and at entrances. It is a self leveling material with unique style and personality.
CLEANING	The tools are recommended to be cleaned immediately after

	use with water.
HEALTH AND SAFETY	Read the label before use. Use a face mask and gloves. <i>Non-Toxic</i>
GENERAL INFORMATION	Note that the technical application and the experience of work teams will affect the final aesthetic result of the floor.  The information and in particular the recommendations relating to the application and final use of products «STYLE BETON» given in good faith, based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual application conditions are such that no guarantee can be given in respect of merchantability or fitness for a particular purpose and no liability of any legal relationship can be established against the company based here in labeling information, written recommendations, or other advice offered. Respect the rights of others is essential. Users must always refer to the most recent version of this.  STYLE BETON  Navarinou 8, Kalochori, Thessaloniki, Greece, 57009 TEL.: 0030 2310 - 920831, FAX: 0030 2310 - 920832, www.stylebeton.com, info@stylebeton.com